


LED Profile Light

Product Code
ARCIPL3BA16W24V



| | |
|----------------------|--------------------------------------|
| IP rating | 20 |
| Ik rating | 6 |
| Source type | Hight power LED |
| Source life time | >50,000h at 25°C ambient temperature |
| CRI | >80 |
| Step McAdam | 3 |
| Source flux | 1920 lm |
| Source efficiency | 120 lm/W |
| Delivered flux | 1600 lm |
| Delivered efficiency | 100 lm/W |
| Input power | 16W/M |
| Supply voltage | DC24V |
| Insulation Class | insulation class III |
| Power supply | constant voltage driver |
| Material | aluminium+PC |
| Light colour/CCT | 2700K/3000K/4000K/6000K |
| Beam angle | diffuse |
| Mounting | recessed/surface mount |
| Reflector color | - |
| Finishing | black/silvery |

Technical drawing



Temperature limits

| | |
|---------------------|----------------|
| Working temperature | -30C° to +50C° |
| Storage temperature | -50C° to +80C° |


Light control

ON/off,optional DALI dimming

Construction

Aluminum shell, anodized, rust and corrosion resistant, fast heat dissipation, PC lampshade, stainless steel buckle, can be cut according to requirements


Photometrics



Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

Specifications



OPTILUX LIGHTING

Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately.
Copyright © 2024 FANGTIAN TECHNOLOGY LLC.