ΟΡΤΙLUX


Datasheet

Festoon Light


Product Code OPTOFTL2W220V



Technical drawing



Photometrics



IP rating Ik rating Source type Source life time CRI Step McAdam Source flux Source efficiency **Delivered flux Delivered efficiency** Input power Supply voltage **Insulation Class** Power supply Material Light colour/CCT Beam angle Mounting Base Finishing

65 4 Hight power LED >50,000h at 25°C ambient temperature >80 3 240 Im 120 lm/W 240lm 120lm/W 2W 220V AC insulation class III Built in constant current PVC+PC 2700K 360° Suspension E27 black

Temperature limits

Working temperature - Storage temperature -

-30C° to +50C° -50C° to +80C°

Light control

ON/off,Phase dimming

Construction

This product features a robust construction designed for outdoor durability, utilizing UV-resistant PVC material for the main casing, highly conductive copper wiring for reliable performance, and an IP65 waterproof rating for protection against dust and water jets; additionally, the light bulb is made from shatterproof PC material, ensuring longevity and safety.

Warranty

- 3-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional

surge protection at the electrical distribution panel

Specifications



OPTILUX LIGHTING

Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately. Copyright © 2024 FANGTIAN TECHNOLOGY LLC.